

A++



STENSKI MODELI



TUNDRA Green PLUS WI-FI (R32) 09 A++ / A+
 TUNDRA Green PLUS WI-FI (R32) 12 A++ / A+
 TUNDRA Green PLUS WI-FI (R32) 18 A++ / A+
 TUNDRA Green PLUS WI-FI (R32) 24 A++ / A+



Wi-Fi control



Frost clean



Super quiet



Intelligent air



Comfortable sleep



Auto restart



-15°C heating



-10°C cooling



On-Off card opcija

Model TUNDRA GREEN PLUS WI-FI			Notranja	AS25TADHRA-CL	AS35TADHRA-CL	AS50TDDHRA-CL	AS68TEBHRA-CL
			Zunanja	1U25BEEFRA	1U35MEEFRA	1U50JMEEFRA	1U68REFFRA
HLAJENJE	Moč	Nominalno (Min.-Max.)	kW	2,6 (0,8-3,4)	3,6 (1,0-4,0)	5,0 (1,3-5,8)	7,0 (2,2-8,5)
	Energetska učinkovitost / razred	SEER koeficient		6,2 / 3,23 (A++)	6,4 / 3,23 (A++)	6,1 / 3,41 (A++)	7,1 / 3,23 (A++)
	Moč električnega priključka	Nominalno (Min.-Max.)	kW	0,80 (0,30-1,20)	1,11 (0,30-1,60)	1,46 (0,40-2,00)	2,16 (0,70-2,90)
	Temperaturni razpon delovanja (Hlajenje)	Min. - Max.	°C	-15-43 °C(out)	-15-43 °C(out)	-15-43 °C(out)	-15-43 °C(out)
OGREVANJE	Moč	Nominalno (Min.-Max.)	kW	2,9 (1,0-3,8)	3,7 (1,1-4,6)	5,2 (1,4-6,0)	8,1 (2,4-10,0)
	Energetska učinkovitost / razred	SCOP koeficient		4,0 / 3,71 (A+)	4,1 / 3,71 (A+)	4,0 / 3,71 (A+)	4,0 / 3,71 (A+)
	Moč električnega priključka	Nominalno (Min.-Max.)	kW	0,78 (0,30-1,50)	0,99 (0,40-1,60)	1,40 (0,52-2,5)	2,18 (0,70-2,90)
	Temperaturni razpon delovanja (Gretje)	Min. - Max.	°C	-25-24 °C(out)	-25-24 °C(out)	-25-24 °C(out)	-25-24 °C(out)
Napajanje	Ph/V/Hz			1/230/50	1/230/50	1/230/50	1/230/50
Napajanje (pozicija)				zunanja (3x1,5)	zunanja (3x1,5)	zunanja (3x1,5)	zunanja (3x2,5)
Notranja enota							
Neto dimenzije	Š/D/V	mm		820/195/280	820/195/280	1008/225/318	1125/240/335
Dimenzije z embalažo	Š/D/V	mm		909/279/355	909/279/355	1085/329/403	1206/342/418
Neto / bruto teža		kg		8,8/11	8,8/11	11,6/14,4	14/17,5
Pretok zraka (Hlajenje/Gretje)	Max.	m³/h		500	550	1000	1200
Razvlaževanje		lit/h		1,2	1,6	2,0	2,8
Raven zvočne moči	(H/Mid/Lo/So)	db(A)		37/32/28/20	38/33/29/21	44/40/35/28	47/43/37/30
Zunanja enota							
Neto dimenzije	Š/D/V	mm		780/245/540	800/280/550	800/280/550	890/353/697
Dimenzije z embalažo	Š/D/V	mm		920/361/620	954/409/625	954/409/625	1046/460/780
Neto / bruto teža		kg		27/30	28/31	33,5/36	51/56
Pretok zraka (Hlajenje/Gretje)	Max.	m³/h.		1900	1900	2500	2900
Raven zvočne moči	Hi	db(A)		47/48	48/49	53/54	52/53
Napajanje	Max.	A		6,7	7,1	8,9	13
Vrsta hladiva	R410 / R32			R32	R32	R32	R32
Količina hladiva	R410 / R32	g		500	620	900	1200
Premeri cevi	Tekočinski	mm		6,35	6,35	6,35	6,35
	Plinski	mm		9,52	9,52	12,7	12,7
	Max. dovoljena dolžina cevovoda	m		15	15	25	25
	Max. višinska razlika	m		10	10	15	15
Komunikacija		mm²		4x1,5	4x1,5	4x1,5	4x1,5
Razmak nogic		mm		500	500	510	

* Modeli AS25TABHRA, AS35TABHRA, AS50TDBHRA, AS68TEBHRA ne vključujejo WI-FI modula