

ZUBADAN
New Generation

R32

PUD-SHWM

NOVO

			PUD-SHWM80VAA	PUD-SHWM80YAA	PUD-SHWM100YAA	PUD-SHWM120YAA	PUD-SHWM140YAA
Dimenzije V x Š x G	mm		1020x1050x480	1020x1050x480	1020x1050x480	1020x1050x480	1020x1050x480
Masa	kg		102	115	121	121	122
Električno napajanje (V / faze / Hz)			230/1f/50	400/3f/50	400/3f/50	400/3f/50	400/3f/50
Gretje	A7W35	nazivna	6,0	6,0	8,0	10,0	12,0
		COP	5,03	5,03	5,00	4,80	4,70
	A2W35	nazivna	8,0	8,0	10,0	12,0	14,0
		COP	3,75	3,75	3,45	3,30	3,05
	A-7W35	nazivna	8,0	8,0	10,0	12,0	14,0
		COP	3,14	3,14	3,05	2,85	2,70
Srednje podnebje, izhod vode 35 °C	Razred učinkovitosti *		A+++	A+++	A+++	A+++	A+++
	η _S		181	181	180	179	179
	SCOP		4,53	4,53	4,50	4,48	4,48
Srednje podnebje, izhod vode 55 °C	Razred učinkovitosti *		A++	A++	A++	A++	A++
	η _S		128	128	136	135	134
	SCOP		3,20	3,20	3,40	3,38	3,35
Sanitarna voda 200 l profil L	Razred učinkovitosti		A+ / A	A+ / A	A+ / A	A+ / A	A+ / A
	η _{WH}		148 / 121	148 / 121	148 / 121	148 / 121	145 / 121
	MFT (°C)		60	60	60	60	60
Hlajenje	A35W7	nazivna	Enote niso namenjene hlajenju				
		EER					
	A35W18	nazivna					
		EER					
Zvočna moč (PWL) pri gretju	dB(A)		56	56	60	60	62
Največji tok delovanja	A		22,0	8,0	10,0	12,0	12,0
Varovalka	A		25	16	16	16	16
Cevne povezave	Premer tekočina / plin	mm	6,35 / 12,7	6,35 / 12,7	6,35 / 12,7	6,35 / 12,7	6,35 / 12,7
	Razdalja zun-not	m	2 - 30	2 - 30	2 - 30	2 - 30	2 - 25
	Višina zun-not	m	max 30	max 30	max 30	max 30	max 25
Hladilno sredstvo	tip / količina kg		R32 / 1,4	R32 / 1,4	R32 / 1,7	R32 / 1,7	R32 / 1,7
GWP / ekvivalent CO ₂	t		675 / 0,945	675 / 0,945	675 / 1,1475	675 / 1,1475	675 / 1,1475
Zajamčeno območje delovanja	gretje	°C	-28 do +24	-28 do +24	-28 do +24	-28 do +24	-28 do +24
	STV	°C	-28 do +35	-28 do +35	-28 do +35	-28 do +35	-28 do +35
	hlajenje	°C	/	/	/	/	/

* Razred energetske učinkovitosti je naveden skladno z Uredbo EU 813/2013

Zajamčeno delovanje do -28 °C

[8, 10, 12 in 14 kW]
(A2/W35)

Modeli: PUD-SHWM80VAA
PUD-SHWM80/100/120/140YAA

